NSN 5935-00-410-5120



Electrical Receptacle Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-410-5120 **Body Style:** Straight shape **Overall Length:** 0.954 inches **Overall Height:** 3.110 inches **Overall Width:** 2.783 inches **Unthreaded Mounting Hole Diameter:** 0.120 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 1.437 inches **Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:** 2.000 inches

Distance From Mounting Shoulder To Front Face:

0.766 inches

Mating End Quantity:

2 **Contact Position Arrangement Style:**

67 all mating ends

Contact Removability:

Removable all mating ends all contact groupings

Contact Maximum Current Rating In Amps:

7.5 2nd mating end 2nd contact grouping

Polarization Method:

3 polarization posts

Shell Type:

Solid

Connector Locking Method:

Spring friction

Terminal Location:

Back all mating ends all contact groupings

Contact Material:

Copper all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and silver all mating ends all contact groupings

Insert Material:

Plastic diallyl phthalate all mating ends

Terminal Type:

Crimp all mating ends all contact groupings

Guide Design And Location:

Hexagon shape male post left-hand at 6 oclock

NSN 5935-00-410-5120

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium and chromate
Included Contact Quantity:
64 2nd mating end 2nd contact grouping
Included Contact Type:
Round socket all mating ends all contact groupings
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.134 gold grains, troy and 0.134 silver grains, troy
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
MM30hM