## NSN 5935-00-410-7468

Plug-in Electronic Components Socket - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-410-7468 **Body Material:** Plastic **Body Style:** Top mount w/molded saddle **Overall Length:** 2.218 inches **Tempurature Rating:** -55.0 degrees celsius and 100.0 degrees celsius **Overall Height:** 0.907 inches **Overall Width:** 1.343 inches **Mounting Hole Diameter:** Between 0.213 inches and 0.223 inches **Body Mounting Hole Accommodation Diameter:** 1.281 inches **Mounting Hole Style:** Round, w/three mounting holes/slots **Specific Equipment Accommodated:** Relay **Contact Maximum Current Rating In Amps:** 5.0 **Contact Material:** Copper **Contact Surface Treatment:** Gold **Accommodated Contact Quantity:** Center To Center Distance Between Outside Mounting Holes Along Length: 0.750 inches **Center To Center Distance Between Outside Mounting Holes Along Width:** 1.844 inches **Polarization Type:** Off center hole **Projection Length Above Mounting Surface:** 0.281 inches **Mounting Method:** Saddle **Mounting Type For Which Designed:** Chassis

Symmetrical

**Contact Position Arrangement Style:** 

NSN 5935-00-410-7468 Plug-in Electronic Components Socket - Page 2 of 2



Contact Maximum Voltage In Volts And Current Type:
500.0 ac and 500.0 dc
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.020 gold grains, troy
Precious Material:
Gold
Test Data Document:
31349-mil-s-12883 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Furnished Items And Quantity:
3 nut and 3 screw and 3 flat washer
Terminal Type And Quantity:
20 crimp
Specification Data:
31349-mil-s-12883 government specification
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
402300