

View Online at https://aerobasegroup.com/nsn/5935-00-411-5153

# **Body Material:**

Plastic and fiber and glass

Thread Class:

2a

Thread Direction:

**Right-hand** 

### Body Style:

Top mount w/studs

#### Fabrication Method:

Molded

#### **Overall Length:**

1.344 inches

#### **Overall Height:**

0.503 inches

#### **Overall Width:**

0.390 inches

# Mounting Hole Diameter:

0.125 inches

# Body Mounting Hole Accommodation Length:

0.820 inches

### Body Mounting Hole Accommodation Width:

0.420 inches

### **Distance Between Mounting Facility Centers:**

1.078 inches

#### Mounting Hole Style:

Rectangular, w/two mounting holes/slots

#### Specific Equipment Accommodated:

Socket relay

#### **Contact Maximum Current Rating In Amps:**

3.0

### **Contact Material:**

Beryllium copper

# **Contact Surface Treatment:**

Gold and silver

# Accommodated Contact Quantity:

14

#### Mounting Method:

Threaded stud

### Mounting Type For Which Designed:

Chassis

### Thready Qty Per Inch (tpi):

40



Thread Size:
0.112 inches
Contact Position Arrangement Style:
Dual in-line
Contact Maximum Voltage In Volts And Current Type:
1500.0 ac and 1500.0 dc
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material And Weight:
0.014 gold grains, troy and 0.014 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unc
Terminal Type And Quantity:
14 tab, solder lug
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A02300