## NSN 5935-00-412-1247

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-412-1247

**Thread Class:** 

2b

**Thread Direction:** 

Right-hand

**Body Style:** 

Straight shape w/cable clamp

**Overall Length:** 

Between 1.480 inches and 1.520 inches

**Bushing Diameter:** 

Between 0.760 inches and 0.800 inches

**Overall Height:** 

Between 1.182 inches and 1.192 inches

**Overall Width:** 

Between 1.182 inches and 1.192 inches

**Unthreaded Mounting Hole Diameter:** 

Between 0.120 inches and 0.130 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 0.901 inches and 0.911 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 0.901 inches and 0.911 inches

Cable Entrance Diameter:

Between 0.435 inches and 0.455 inches

**Distance From Mounting Shoulder To Front Face:** 

Between 1.057 inches and 1.067 inches

**Threaded Device Type:** 

Coupling facility

**Mating End Quantity:** 

1

**Contact Position Arrangement Style:** 

N single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

1000.0 single mating end single contact grouping

**Contact Maximum Frequency Rating:** 

11000.0 megahertz single mating end single contact grouping

Shell Type:

Solid

**Connector Locking Method:** 

Internally threaded coupling ring

**Connector Cable Strain Relief Method:** 

Compression nut

## NSN 5935-00-412-1247

Electrical Receptacle Connector - Page 2 of 2



Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
24
Thread Size:
0.625 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and nickel single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact surface gold
Precious Material And Weight:
0.005 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0