

View Online at <https://aerobasegroup.com/nsn/5935-00-412-8546>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Angle, shape, internal coupling

Overall Length:

1.625 inches

Overall Height:

1.219 inches

Overall Diameter:

0.812 inches

Environmental Protection:

Shock proof and vibration proof

Cable Entrance Diameter:

0.257 inches

Threaded Device Type:

Coupling facility

Mating End Quantity:

1

Contact Position Arrangement Style:

N single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut

Connector Cable Strain Relief Method:

Compression nut

Thready Qty Per Inch (tpi):

24

Thread Size:

0.625 inches

Terminal Location:

Side single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Contact Surface Treatment Specification:

Mil-g-45204, type 2, cl 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Copper alloy

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold

Precious Material And Weight:

0.005 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.