# NSN 5935-00-413-0610

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-413-0610

#### **Environmental Protection:**

Moisture resistant

## **Mating End Quantity:**

1

#### **Contact Removability:**

Nonremovable single mating end single contact grouping

#### Shell Type:

Solid

#### **Connector Locking Method:**

Bayonet shell

#### **Terminal Location:**

Back single mating end single contact grouping

#### **Contact Material:**

Copper alloy single mating end single contact grouping

#### **Contact Surface Treatment:**

Gold single mating end single contact grouping and nickel single mating end single contact grouping

#### **Insert Material:**

Glass single mating end

## **Contact Surface Treatment Specification:**

Mil-g-45204, type 2, class 1 military specification single treatment response single mating end single contact grouping and qq-n-290, class 1, type 7 federal specification single treatment response single mating end single contact grouping

#### **Terminal Type:**

Tab, solder lug single mating end single contact grouping

#### **Contact Material Specification:**

Qq-b-626 federal specification single material response single mating end single contact grouping

# **Shell Material:**

Copper alloy

# **Shell Surface Treatment:**

Gold and nickel

#### **Shell Surface Treatment Specification:**

Mil-g-45204, type 2, class 1 military specification single treatment response and qq-n-290, class 1, type 7 federal specification single treatment response

#### **Shell Material Specification:**

Qq-b-626, comp 22 federal specification single material response

#### **Included Contact Quantity:**

1 single mating end single contact grouping

# **Bushing Accommodation Hole Shape:**

Round

# **Included Contact Type:**

Round pin single mating end single contact grouping

#### Shelf Life:

N/a

#### **Unit Of Measure:**

--

# NSN 5935-00-413-0610

Electrical Receptacle Connector - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.