## NSN 5935-00-413-1059

Tip Jack - Page 1 of 2

**Thread Class:** 





2a **Thread Direction: Right-hand Electrical Insulation Feature:** Insulated from panel **Identification Code Color:** Orange **Body Style:** Threaded bushing mounted **Overall Length:** 0.688 inches Mounting Bushing Length: 0.250 inches **Body Length:** 0.528 inches **Overall Diameter:** 0.406 inches **Bushing Accommodation Hole Shape:** Round Maximum Voltage Rating In Volts: 2000.0 ac Accommodated Finger Type: Test prod single finger **Finger Accommodation Diameter:** 0.080 inches single finger Finger Accommodation Length: 0.388 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.281 inches **Current Rating In Amps:** 15.0 Mounting Facility Type And Quantity: 1 bushing **Thread Size:** 0.250 inches **Terminal Type:** Turret Material: Plastic, diallyl phthalate insulator Material: Plastic diallyl phthalate insulator

## NSN 5935-00-413-1059

Tip Jack - Page 2 of 2



Precious Material And Location: Spring surface gold Precious Material: Gold Surface Treatment: Gold spring Surface Treatment:

Gold spring

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A03400