## NSN 5935-00-413-1231

Tip Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-413-1231 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated completely **Identification Code Color:** Yellow **Body Style:** Threaded bushing mounted **Overall Length:** Between 0.922 inches and 1.000 inches **Mounting Bushing Length:** Between 0.375 inches and 0.438 inches **Body Length:** 0.672 inches **Overall Diameter:** 0.406 inches **Bushing Accommodation Hole Shape:** Round **Maximum Voltage Rating In Volts:** 2000.0 ac **Accommodated Finger Type:** Test prod single finger **Finger Accommodation Diameter:** 0.080 inches single finger **Finger Accommodation Length:** 0.500 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.250 inches **Current Rating In Amps: Mounting Facility Type And Quantity:** 1 bushing

**Thread Size:** 0.250 inches **Terminal Type:** Tab, solder lug Material: Plastic, polyamide insulator Material: Plastic polyamide insulator

# NSN 5935-00-413-1231

Tip Jack - Page 2 of 2



_	•		_			
<u>ن</u>	irta	$\sim$	Irο	atm	nan	
υı	ai ia	ᅜ	116	аш		ı.,

Any acceptable spring

#### **Test Data Document:**

81349-mil-c-39024 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Thread Series Designator:**

Unef

#### **Specification Data:**

81349-mil-c-39024 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A03400