## NSN 5935-00-414-1277

**Included Contact Quantity:** 

25 single mating end single contact grouping

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-414-1277

**Body Style:** Straight shape **Overall Length:** 1.369 inches **Overall Height:** Between 0.368 inches and 0.372 inches Overall Width: 0.275 inches **Environmental Protection:** Moisture resistant and vibration resistant and shock resistant **Unthreaded Mounting Hole Diameter:** 0.140 inches **Distance Between Mounting Facility Centers:** 1.094 inches **Mating End Quantity: Contact Position Arrangement Style:** 25 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 3.0 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 1000.0 single mating end single contact grouping **Polarization Method:** Mating end **Connector Locking Method:** Friction **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Insert Material Specification:** Mil-m-14 ty sdg military specification single material response single mating end

## NSN 5935-00-414-1277

Electrical Receptacle Connector - Page 2 of 2



Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.025 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.