NSN 5935-00-415-2007

Electrical Receptacle Connector - Page 1 of 1



| View Online at https://aerobasegroup.com/nsn/5935-00-415-2007 |
|---|
| Thread Class: |
| 2a |
| Body Style: |
| Straight shape, external coupling |
| Overall Length: |
| 0.375 inches |
| Bushing Diameter: |
| 0.250 inches |
| Overall Height: |
| 0.500 inches |
| Overall Width: |
| 0.500 inches |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| 0.340 inches |
| Distance From Mounting Shoulder To Front Face: |
| 0.310 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Contact Maximum Ac Voltage Rating In Volts: |
| 500.0 single mating end single contact grouping |
| Contact Maximum Frequency Rating: |
| 10000.0 megahertz single mating end single contact grouping |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Externally threaded shell |
| Radio Frequency Type Contact Characteristic Impedance In Ohms: |
| 50.0 single mating end single contact grouping |
| Included Contact Quantity: |
| 1 single mating end single contact grouping |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| Demilitarization: |
| No |
| Fiig: |

A039b0