Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-415-4721

| т | Thread Class: | | |
|---|-----------------------------------------------------------------------------|--|--|
| | | | |
| | 2a Thread Direction: | | |
| - | | | |
| | Right-hand | | |
| | Body Style: | | |
| | Straight shape, external coupling | | |
| | Overall Length: | | |
| | Between 1.275 inches and 1.340 inches | | |
| | Dverall Height: | | |
| | Between 0.929 inches and 0.945 inches | | |
| | Overall Width: | | |
| | Between 0.929 inches and 0.945 inches | | |
| | Environmental Protection: | | |
| | Heat resistant and moisture proof and vibration resistant | | |
| | Inthreaded Mounting Hole Diameter: | | |
| | Between 0.116 inches and 0.126 inches | | |
| C | Center To Center Distance Between Mounting Facilities Parallel To Height: | | |
| E | Between 0.714 inches and 0.724 inches | | |
| C | Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: | | |
| E | Between 0.714 inches and 0.724 inches | | |
| C | Distance From Mounting Shoulder To Front Face: | | |
| E | Between 0.765 inches and 0.775 inches | | |
| Т | Fhreaded Device Type: | | |
| E | Back shell | | |
| Ν | Nating End Quantity: | | |
| 1 | | | |
| C | Contact Position Arrangement Style: | | |
| 1 | 0-5 single mating end | | |
| C | Contact Removability: | | |
| F | Removable single mating end single contact grouping | | |
| F | Polarization Method: | | |
| k | Key, multiple key groove | | |
| h | nsert Position In Deg: | | |
| 2 | 258.0 and 228.0 and 112.0 and 40.0 | | |
| S | Shell Type: | | |
| S | Solid | | |
| C | Connector Locking Method: | | |
| E | Bayonet pin | | |
| Т | Fhready Qty Per Inch (tpi): | | |
| 2 | 28 | | |
| Т | Thread Size: | | |
| С | 0.625 inches | | |

Electrical Receptacle Connector - Page 2 of 2



| Terminal Location: | |
|-----------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Back single mating e | nd single contact grouping |
| Contact Material: | |
| Copper alloy single r | nating end single contact grouping |
| Contact Surface Tre | eatment: |
| Gold single mating e | nd single contact grouping |
| Contact Surface Tr | eatment Specification: |
| Mil-g-45204, type 1, | class 2 military specification single treatment response single mating end single contact grouping |
| Terminal Type: | |
| Crimp single mating | end single contact grouping |
| Shell Material: | |
| Aluminum alloy 6061 | |
| Shell Surface Treat | nent: |
| Chromium | |
| Shell Material Spec | fication: |
| Qq-a-367, comp 606 | 1, t6 federal specification single material response |
| Included Contact Q | uantity: |
| 5 single mating end | ingle contact grouping |
| Included Contact T | ире: |
| Round socket single | mating end single contact grouping |
| Precious Material A | nd Location: |
| Contact surfaces gol | t de la constante de |
| Precious Material A | nd Weight: |
| 0.025 gold grains, tr | ру |
| Precious Material: | |
| Gold | |
| Test Data Documen | t: |
| 81349-mil-c-81511 s | pecification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes cor | nmercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and p | erformance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Thread Series Desig | gnator: |
| Un | |
| Specification Data: | |
| 81349-mil-c-81511/1 | government specification |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A039b0 | |
| Mil-std (military Sta | ndard): |
| Mil-g-45204 spec. | |