

NSN 5935-00-415-5402 Electrical Plug Connector - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-415-5402 **Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.420 inches **Overall Diameter:** 1.777 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 24-61 single mating end

**Contact Removability:** 

Removable single mating end single contact grouping

**Contact Maximum Ac Voltage Rating In Volts:** 

600.0 single mating end single contact grouping

**Polarization Method:** 

Keyway or multiple keyway

**Insert Position In Deg:** 

0.0

Shell Type:

Solid

**Connector Locking Method:** 

Bayonet latch

**Thread Length:** 

0.290 inches

Thread Size:

1.438 inches

**Terminal Location:** 

Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

**Contact Surface Treatment Specification:** 

Mil-g-45204 military specification single treatment response all mating ends all contact groupings

## **NSN 5935-00-415-5402**Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Included Contact Quantity:
61 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.061 gold grains, troy
Precious Material:
Gold
Test Data Document:
81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Thread Series Designator:
Unef
Specification Data:
96906-ms3476 government standard
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.