NSN 5935-00-416-6003

Thread Class:

Right-hand

Thread Direction:

2a

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-416-6003

Body Style:
Straight shape, external coupling
Overall Length:
0.844 inches
Environmental Protection:
Pressure proof and shock resistant and thermal shock resistant and salt water resistant
Distance From Mounting Shoulder To Front Face:
0.281 inches
Threaded Device Type:
Coupling facility and mounting bushing
Mating End Quantity:
1
Contact Position Arrangement Style:
Nonstd single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
1.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1800.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Externally threaded shell
Connector Cable Strain Relief Method:
Compression nut
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thread Size:
0.375 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end

NSN 5935-00-416-6003

A039b0

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Contact Material Specification:
Qq-b-626, comp 22, 1/2 h federal specification single material response single mating end single contact grouping
Shell Material:
Copper alloy
Shell Surface Treatment:
Gold and copper
Shell Material Specification:
Qq-b-626, comp 22, 1/2 h federal specification single material response
Included Contact Quantity:
1 single mating end single contact grouping
Bushing Accommodation Hole Shape:
Round
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact and shell surfaces gold
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig: