NSN 5935-00-419-1414



Connector Adapter - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5935-00-419-1414 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.594 inches **Overall Diameter:** 0.813 inches **Environmental Protection:** Weatherproof **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** N all mating ends **Contact Removability:** Nonremovable all mating ends single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 500.0 all mating ends single contact grouping Shell Type: Solid **Connector Locking Method:** Externally threaded shell and internally threaded coupling ring Radio Frequency Type Contact Characteristic Impedance In Ohms: 50.0 all mating ends single contact grouping Thready Qty Per Inch (tpi): 24 **Thread Size:** 0.625 inches **Contact Material:** Copper alloy all mating ends single contact grouping **Contact Surface Treatment:** Silver all mating ends single contact grouping **Insert Material:** Plastic polytetrafluoroethylene all mating ends **Shell Material:**

Copper alloy **Shell Surface Treatment:** Silver

NSN 5935-00-419-1414

Connector Adapter - Page 2 of 2



Included Contact Quantity:
1 2nd mating end single contact grouping

1 Zila mating ona omgle contact gi

Included Contact Type:

Coaxial socket 2nd mating end single contact grouping

Precious Material And Location:

Contact and body surfaces silver

Precious Material And Weight:

0.110 silver grains, troy

Precious Material:

Silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0