NSN 5935-00-419-3676

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-419-3676

Body Style:
Angle shape, internal coupling
Overall Length:
1.752 inches
Overall Height:
1.530 inches
Overall Diameter:
1.510 inches
Environmental Protection:
Salt water resistant and moisture resistant and pressure proof and vibration resistant
Mating End Quantity:
1
Contact Position Arrangement Style:
20-39 single mating end
Contact Removability:
Removable single mating end all contact groupings
Contact Maximum Current Rating In Amps:
7.5 single mating end 2nd contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1500.0 single mating end all contact groupings
Contact Maximum Dc Voltage Rating In Volts:
2100.0 single mating end 1st contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Potting
Connector Locking Method:
Bayonet latch
Connector Cable Strain Relief Method:
Potting type
Terminal Location:
Back single mating end all contact groupings
Contact Material:
Copper alloy single mating end all contact groupings
Contact Surface Treatment:
Gold single mating end all contact groupings and silver single mating end all contact groupings
Insert Material:
Rubber single mating end
Terminal Type:
Solder well single mating end all contact groupings

NSN 5935-00-419-3676Electrical Plug Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
37 single mating end 2nd contact grouping
Included Contact Type:
Round pin single mating end all contact groupings
Precious Material And Location:
Contact surface gold and contact surface silver
Precious Material And Weight:
$0.039 \ \text{gold grains}, \ \text{troy} \ \text{and} \ 0.039 \ \text{silver grains}, \ \text{troy}$
Precious Material:
Gold and silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Δ039h0