NSN 5935-00-419-3709

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-419-3709

Thread Class: 2b
2b
Thread Direction:
Right-hand
Overall Length:
Between 8.604 inches and 8.614 inches
Overall Height:
Between 4.604 inches and 4.614 inches
Overall Diameter:
2.781 inches
Body Angle In Deg:
75.0
Environmental Protection:
Moisture resistant and salt water resistant and vibration resistant
Cable Entrance Diameter:
Between 1.188 inches and 1.625 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
36-10 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
Contact Maximum Current Rating In Amps: 22.0 single mating end single contact grouping
•
22.0 single mating end single contact grouping
22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts:
22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping
22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method:
22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway
22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg:
22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 125.0
22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 125.0 Shell Type:
22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 125.0 Shell Type: Solid
22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 125.0 Shell Type: Solid Connector Locking Method:
22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 125.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring
22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 125.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method:
22.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 500.0 single mating end single contact grouping Polarization Method: Keyway or multiple keyway Insert Position In Deg: 125.0 Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Cable clamp

16

NSN 5935-00-419-3709Electrical Plug Connector - Page 2 of 2



Thread Size:
2.250 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping
Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy 2024
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Shell Material Specification:
Qq-a-225/6, alloy 2024 federal specification single material response
Included Contact Quantity:
48 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.048 gold grains, troy and 0.048 silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Un
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0