

View Online at <https://aerobasegroup.com/nsn/5935-00-419-7288>

Thread Class:

2a and 2a and 2a

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

Straight shape, external coupling

Overall Length:

1.240 inches

Overall Diameter:

2.078 inches

Distance From Mounting Shoulder To Front Face:

0.781 inches

Mounting Facility Thickness:

Between 0.062 inches and 0.125 inches

Threaded Device Type:

Back shell and coupling facility and mounting bushing

Mating End Quantity:

1

Contact Position Arrangement Style:

22-55 single mating end

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

18.0 and 149.0 and 192.0 and 259.0

Shell Type:

Solid

Connector Locking Method:

Externally threaded shell

Thread Size:

1.312 inches and 1.437 inches and 1.500 inches

Insert Material:

Plastic single mating end

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Anodize

Bushing Accommodation Hole Shape:

Round

Test Data Document:

94756-414-1939 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:

Unef and unef and unef

Specification Data:

94756-414-1939-057 manufacturers specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0