## NSN 5935-00-420-7423

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-420-7423
Body Style:
Straight type
Overall Length:
4.470 inches
Overall Width:
0.470 inches
Distance Between Mounting Facility Centers:
4.063 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
29 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
750.0 single mating end single contact grouping
Shell Type:
Solid
Connector Locking Method:
Friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:

Turret single mating end single contact grouping

**Shell Material:** 

Aluminum

**Shell Surface Treatment:** 

Cadmium and iridium

**Shell Material Specification:** 

Qq-a-591 federal specification single material response

**Insert Material Specification:** 

Mil-m-14, type mdg military specification single material response single mating end

**Shell Guide Type And Location Designator:** 

A slot

## NSN 5935-00-420-7423

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity:
29 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.029 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A039b0

Mil-m-14 spec.

Mil-std (military Standard):