## NSN 5935-00-421-5886

**Thread Class:** 

Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-421-5886



2a **Thread Direction:** Right-hand **Body Style:** Straight shape, external coupling **Overall Length:** 0.891 inches **Overall Diameter:** Between 1.046 inches and 1.078 inches **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 7p single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Contact Maximum Dc Voltage Rating In Volts:** 850.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 0.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin Thready Qty Per Inch (tpi): **Thread Size:** 0.562 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping and silver single mating end single contact grouping **Insert Material:** Plastic silicone single mating end

## **NSN 5935-00-421-5886**Electrical Plug Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
7 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold and contact surfaces silver
Precious Material And Weight:
0.007 gold grains, troy and $0.007$ silver grains, troy
Precious Material:
Gold and silver
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0