NSN 5935-00-421-5936

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-421-5936

Thread Class:
2b
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
Between 0.865 inches and 0.907 inches
Overall Diameter:
Between 0.765 inches and 0.781 inches
Threaded Device Type:
Coupling facility
Mating End Quantity:
1
Contact Position Arrangement Style:
N single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1000.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thready Qty Per Inch (tpi):
24
Thread Size:
0.625 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Insert Material:
Rubber single mating end

Rubber single mating end

NSN 5935-00-421-5936

Electrical Plug Connector - Page 2 of 2



Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 2 military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Contact Material Specification:

Qq-b-626 federal specification single material response single mating end single contact grouping

Shell Material:

Copper alloy

Shell Surface Treatment:

Silver

Shell Material Specification:

Qq-b-626 federal specification single material response

Included Contact Quantity:

1 single mating end single contact grouping

Included Contact Type:

Coaxial pin single mating end single contact grouping

Precious Material And Location:

Contact surface gold and shell surface silver

Precious Material And Weight:

0.005 gold grains, troy and 0.105 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig: A039b0

Mil-std (military Standard):

Mil-g-45204 spec.