## NSN 5935-00-421-6005

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-421-6005 **Thread Class:** 2a and 2b **Thread Direction:** Right-hand **Body Style:** Rectangular shape **Overall Length:** 2.890 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 2.371 inches and 2.379 inches **Overall Height:** 1.640 inches **Overall Width:** 1.670 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 0.870 inches and 0.880 inches **Threaded Device Type:** Coupling facility **Mating End Quantity: Contact Position Arrangement Style:** 70 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 13.0 single mating end single contact grouping **Polarization Method:** Jackscrew Shell Type: Solid **Connector Locking Method:** Jackscrew-socket Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.138 inches **Terminal Location:** Back single mating end single contact grouping

**Contact Material:** 

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:** 

Gold single mating end single contact grouping

## NSN 5935-00-421-6005

Electrical Receptacle Connector - Page 2 of 2



single contact grouping

Insert Material:
Plastic single mating end
Contact Surface Treatment Specification:
Mil-g-45204, type 2, cl 1 military specification single treatment response single mating end single
Terminal Type:
Wire wrap single mating end single contact grouping
Contact Material Specification:
Qq-b-750 federal specification single material response single mating end single contact grouping
Shell Material:
Steel comp 305
Shell Surface Treatment:
Passivate
Shell Surface Treatment Specification:
Mil-f-14072 military specification single treatment response
Shell Material Specification:
Qq-s-763 federal specification single material response
Included Contact Quantity:
70 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.070 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

. ...

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.