NSN 5935-00-421-6066

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-421-6066

Body Style: Straight shape, flush mount **Overall Length:** 0.954 inches **Overall Height:** 3.060 inches **Overall Width:** 2.310 inches **Environmental Protection:** Moisture resistant and salt water resistant and vibration resistant Center To Center Distance Between Mounting Facilities Parallel To Height: Between 0.745 inches and 0.755 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: Between 2.057 inches and 2.067 inches **Distance From Mounting Shoulder To Front Face:** 0.125 inches **Mating End Quantity:** 2 **Contact Position Arrangement Style:** 57 all mating ends **Contact Removability:** Nonremovable all mating ends single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 all mating ends single contact grouping Shell Type: Solid **Terminal Location:** Back all mating ends single contact grouping **Contact Material:** Copper alloy all mating ends single contact grouping **Contact Surface Treatment:** Gold all mating ends single contact grouping and silver all mating ends single contact grouping **Insert Material:** Plastic polytetrafluoroethylene all mating ends **Terminal Type:** Solder well all mating ends single contact grouping **Shell Material:** Aluminum alloy **Shell Surface Treatment:** Cadmium

Included Contact Type:

Round socket all mating ends single contact grouping

NSN 5935-00-421-6066

Electrical Receptacle Connector - Page 2 of 2



Precious Material And Location:

Contact surfaces gold and contact surfaces silver

Precious Material And Weight:

0.114 gold grains, troy and 0.114 silver grains, troy

Precious Material:

Gold and silver

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0