

View Online at <https://aerobasegroup.com/nsn/5935-00-421-8340>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight type

Overall Length:

1.524 inches

Overall Height:

0.338 inches

Overall Width:

0.218 inches

Environmental Protection:

Heat resistant and cold resistant and vibration resistant and shock resistant and moisture resistant and corrosion resistant

Distance Between Mounting Facility Centers:

1.370 inches

Threaded Device Type:

Mounting hole

Mating End Quantity:

1

Contact Position Arrangement Style:

2 rows of contacts non-inserted board single mating end

Contact Removability:

Nonremovable single mating end 2nd contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end 2nd contact grouping

Polarization Method:

Contact

Connector Locking Method:

Friction

Thread Size:

0.060 inches

Terminal Location:

Back single mating end 2nd contact grouping

Contact Material:

Copper alloy 172 single mating end 2nd contact grouping

Contact Surface Treatment:

Gold and nickel single mating end 2nd contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2 military specification 1st treatment response and qq-n-290 federal specification 2nd treatment response single mating end 2nd contact grouping

Criticality Code Justification:

Feat

Terminal Type:

Pin single mating end 2nd contact grouping

Contact Material Specification:

Qq-c-530, 1/2 hard federal specification single material response single mating end 2nd contact grouping

Insert Material Specification:

Mil-m-14, ty sdg-f military specification single material response single mating end

Special Features:

Polarizing pin in contact position 10, furnished items- gasket

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.022 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.