## NSN 5935-00-421-8845

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-421-8845

## **Body Style:**

Straight shape, internal coupling w/strain relief

## **Overall Diameter:**

Between 1.188 inches and 1.218 inches

#### **Environmental Protection:**

Moisture resistant and salt water resistant and vibration resistant

## **Mating End Quantity:**

1

## **Contact Position Arrangement Style:**

20 single mating end

## **Contact Removability:**

Removable single mating end single contact grouping

## **Contact Maximum Current Rating In Amps:**

7.5 single mating end single contact grouping

#### **Polarization Method:**

Keyway or multiple keyway

## **Insert Position In Deg:**

285.0

## Shell Type:

Solid

## **Connector Locking Method:**

Spring friction

## **Connector Cable Strain Relief Method:**

Cable clamp

## **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

## **Insert Material:**

Rubber single mating end

## **Terminal Type:**

Crimp single mating end single contact grouping

### **Shell Material:**

Aluminum alloy

## **Shell Surface Treatment:**

Cadmium

## **Included Contact Quantity:**

19 single mating end single contact grouping

## **Included Contact Type:**

Round socket single mating end single contact grouping

# **NSN 5935-00-421-8845**Electrical Plug Connector - Page 2 of 2



<b>Precious Material And Location:</b>
Contact surfaces gold
<b>Precious Material And Weight:</b>
0.019 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A039b0