NSN 5935-00-421-9333

Electrical Receptacle Connector - Page 1 of 2

Tab, solder lug single mating end single contact grouping



View Online at https://aerobasegroup.com/nsn/5935-00-421-9333

Body Style:
Straight shape, external coupling
Overall Length:
0.875 inches
Overall Height:
1.031 inches
Overall Width:
1.031 inches
Unthreaded Mounting Hole Diameter:
0.094 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.844 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.844 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
37-3p single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet pin
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Silver single mating end single contact grouping
Insert Material:
Rubber single mating end
Contact Surface Treatment Specification:
Mil-g-45204 military specification single treatment response single mating end single contact grouping
Terminal Type:

NSN 5935-00-421-9333

Electrical Receptacle Connector - Page 2 of 2



Shell Material:
Aluminum alloy
Shell Surface Treatment:
Tin
Shell Surface Treatment Specification:
Qq-z-325, type 1, cl 2 federal specification single treatment response
Included Contact Quantity:
12 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces silver
Precious Material And Weight:
0.012 silver grains, troy
Precious Material:
Silver
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0
Mil-std (military Standard):
Mil-g-45204 spec.