

View Online at <https://aerobasegroup.com/nsn/5935-00-421-9333>

**Body Style:**

Straight shape, external coupling

**Overall Length:**

0.875 inches

**Overall Height:**

1.031 inches

**Overall Width:**

1.031 inches

**Unthreaded Mounting Hole Diameter:**

0.094 inches

**Center To Center Distance Between Mounting Facilities Parallel To Height:**

0.844 inches

**Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:**

0.844 inches

**Mating End Quantity:**

1

**Contact Position Arrangement Style:**

37-3p single mating end

**Contact Removability:**

Nonremovable single mating end single contact grouping

**Contact Maximum Current Rating In Amps:**

5.0 single mating end single contact grouping

**Polarization Method:**

Keyway or multiple keyway

**Insert Position In Deg:**

0.0

**Shell Type:**

Solid

**Connector Locking Method:**

Bayonet pin

**Terminal Location:**

Back single mating end single contact grouping

**Contact Material:**

Copper alloy single mating end single contact grouping

**Contact Surface Treatment:**

Silver single mating end single contact grouping

**Insert Material:**

Rubber single mating end

**Contact Surface Treatment Specification:**

Mil-g-45204 military specification single treatment response single mating end single contact grouping

**Terminal Type:**

Tab, solder lug single mating end single contact grouping

**Shell Material:**

Aluminum alloy

**Shell Surface Treatment:**

Tin

**Shell Surface Treatment Specification:**

Qq-z-325, type 1, cl 2 federal specification single treatment response

**Included Contact Quantity:**

12 single mating end single contact grouping

**Included Contact Type:**

Round pin single mating end single contact grouping

**Precious Material And Location:**

Contact surfaces silver

**Precious Material And Weight:**

0.012 silver grains, troy

**Precious Material:**

Silver

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A039b0

**Mil-std (military Standard):**

Mil-g-45204 spec.