

View Online at <https://aerobasegroup.com/nsn/5935-00-422-0281>

Thread Class:

2b

Thread Direction:

Right-hand

Body Style:

Straight edge type w/mounting flange

Overall Length:

Between 4.891 inches and 4.921 inches

Overall Height:

0.707 inches

Overall Width:

0.340 inches

Environmental Protection:

Salt water resistant and moisture proof and vibration resistant

Unthreaded Mounting Hole Diameter:

0.112 inches

Distance Between Mounting Facility Centers:

4.500 inches

Board Accommodated Length:

4.067 inches single board

Threaded Device Type:

Mounting hole

Board Accommodated Width:

Between 0.054 inches and 0.071 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

Bridged contacts inserted board single mating end

Contact Removability:

Nonremovable single mating end single contact grouping

Polarization Method:

Inter-contact polarizing keys

Thread Size:

0.112 inches

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping and nickel single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Terminal Type:

Tab, solder lug single mating end single contact grouping

Insert Material Specification:

Mil-m-19833, type gdi-30f military specification single material response single mating end

Included Contact Quantity:

25 single mating end single contact grouping

Included Contact Type:

Bifurcated accordian leaf spring single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.025 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-19833 spec.