Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-422-0283

| Thread Class: |
|---|
| 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Straight edge type w/mounting flange |
| Overall Length: |
| Between 4.891 inches and 4.921 inches |
| Overall Height: |
| 0.707 inches |
| Overall Width: |
| 0.340 inches |
| Unthreaded Mounting Hole Diameter: |
| 0.112 inches |
| Distance Between Mounting Facility Centers: |
| 4.500 inches |
| Board Accommodated Length: |
| 4.067 inches single board |
| Threaded Device Type: |
| Mounting hole |
| Board Accommodated Width: |
| Between 0.054 inches and 0.071 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| Bridged contacts inserted board single mating end |
| Contact Removability: |
| Nonremovable single mating end single contact grouping |
| Polarization Method: |
| Inter-contact polarizing keys |
| Thread Size: |
| 0.112 inches |
| Terminal Location: |
| Back single mating end single contact grouping |
| Contact Material: |
| Copper alloy single mating end single contact grouping |
| Contact Surface Treatment: |
| Gold single mating end single contact grouping and nickel single mating end single contact grouping |
| Insert Material: |
| Plastic diallyl phthalate single mating end |
| Terminal Type: |
| Solder well single mating and single contact grouping |

Solder well single mating end single contact grouping

NSN 5935-00-422-0283

Electrical Receptacle Connector - Page 2 of 2



Insert Material Specification: Mil-m-19833, type gdi-30f military specification single material response single mating end **Included Contact Quantity:** 25 single mating end single contact grouping Included Contact Type: Bifurcated accordian leaf spring single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.025 gold grains, troy **Precious Material:** Gold **Thread Series Designator:** Unc Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0 Mil-std (military Standard): Mil-m-19833 spec.