

View Online at <https://aerobasegroup.com/nsn/5935-00-422-3544>

Thread Class:

2a

Thread Direction:

Right-hand

Body Style:

Straight shape quick connect

Overall Length:

1.094 inches

Overall Width:

0.562 inches

Environmental Protection:

Waterproof

Threaded Device Type:

Mounting bushing

Mating End Quantity:

2

Contact Position Arrangement Style:

Tps all mating ends

Contact Removability:

Nonremovable all mating ends single contact grouping

Contact Maximum Ac Voltage Rating In Volts:

1000.0 all mating ends single contact grouping

Contact Maximum Frequency Rating:

10000.0 megahertz all mating ends single contact grouping

Shell Type:

Solid

Connector Locking Method:

Bayonet pin

Radio Frequency Type Contact Characteristic Impedance In Ohms:

50.0 all mating ends single contact grouping

Thready Qty Per Inch (tpi):

28

Thread Size:

0.438 inches

Contact Material:

Copper alloy all mating ends single contact grouping

Contact Surface Treatment:

Gold all mating ends single contact grouping and silver all mating ends single contact grouping

Insert Material:

Plastic fluorocarbon all mating ends

Shell Material:

Copper alloy

Shell Surface Treatment:

Gold and silver

Included Contact Quantity:

1 all mating ends single contact grouping

Bushing Accommodation Hole Shape:

Round

Included Contact Type:

Coaxial socket all mating ends single contact grouping

Precious Material And Location:

Contact and body surfaces gold and contact and body surfaces silver

Precious Material And Weight:

0.110 gold grains, troy and 0.110 silver grains, troy

Precious Material:

Gold and silver

Thread Series Designator:

Unef

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0