

View Online at <https://aerobasegroup.com/nsn/5935-00-422-5286>

Thread Class:

2a and 2a and 2b

Thread Direction:

Right-hand and right-hand and right-hand

Body Style:

T-shape

Overall Length:

Between 0.900 inches and 0.940 inches

Overall Height:

Between 0.600 inches and 0.640 inches

Overall Width:

Between 0.307 inches and 0.317 inches

Environmental Protection:

Pressure proof and moisture resistant and vibration resistant

Threaded Device Type:

Coupling facility

Mating End Quantity:

3

Contact Position Arrangement Style:

Nonstd all mating ends

Contact Removability:

Nonremovable all mating ends all contact groupings

Contact Maximum Ac Voltage Rating In Volts:

500.0 all mating ends all contact groupings

Shell Type:

Solid

Connector Locking Method:

Internally threaded coupling nut and externally threaded shell

Thready Qty Per Inch (tpi):

36 and 36 and 36

Thread Size:

0.250 inches and 0.250 inches and 0.250 inches

Contact Material:

Copper alloy all mating ends all contact groupings

Contact Surface Treatment:

Gold all mating ends all contact groupings and copper all mating ends all contact groupings

Insert Material:

Plastic tetrafluoroethylene all mating ends

Contact Material Specification:

Qq-b-626, comp 22 federal specification single material response 1st mating end all contact groupings

Shell Material:

Steel comp 303

Shell Surface Treatment:

Gold and nickel

Shell Material Specification:

Qq-s-763, class 303 federal specification single material response

Included Contact Quantity:

1 2nd mating end all contact groupings

Included Contact Type:

Coaxial socket 3rd mating end all contact groupings

Precious Material And Location:

Contact and @shell surfaces gold

Precious Material And Weight:

0.115 gold grains, troy

Precious Material:

Gold

Thread Series Designator:

Uns and uns and uns

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0