AeroBase Group

View Online at https://aerobasegroup.com/nsn/5935-00-423-6707

Overall Length:3.875 inchesOverall Height:4.500 inchesEnvironmental Protection:Explosion proofUnthreaded Mounting Hole Diameter:0.344 inchesDistance Between Mounting Facility Centers:5.000 inchesMating End Quantity:1Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:20.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:250.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:18.0 single mating end single contact groupingPolarization Method:Mating endShell Type:SolidConnector Locking Method:
Overall Height:4.500 inchesEnvironmental Protection:Explosion proofUnthreaded Mounting Hole Diameter:0.344 inchesDistance Between Mounting Facility Centers:5.000 inchesMating End Quantity:1Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:20.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:250.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:18.0 single mating end single contact groupingMating endHoting endShell Type:SolidConnector Locking Method:
4.500 inches Environmental Protection: Explosion proof Unthreaded Mounting Hole Diameter: 0.344 inches Distance Between Mounting Facility Centers: 5.000 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 20.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 250.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 18.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 18.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 18.0 single mating end single contact grouping Solid Connector Locking Method:
Environmental Protection: Explosion proof Unthreaded Mounting Hole Diameter: 0.344 inches Distance Between Mounting Facility Centers: 5.000 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 20.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 250.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 250.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 18.0 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Connector Locking Method:
Explosion proof Unthreaded Mounting Hole Diameter: 0.344 inches Distance Between Mounting Facility Centers: 5.000 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 20.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 250.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 18.0 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Connector Locking Method:
Unthreaded Mounting Hole Diameter:0.344 inchesDistance Between Mounting Facility Centers:5.000 inchesMating End Quantity:1Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:20.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:250.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:18.0 single mating end single contact groupingPolarization Method:Mating endShell Type:SolidConnector Locking Method:
0.344 inches Distance Between Mounting Facility Centers: 5.000 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 20.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 250.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 18.0 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid
Distance Between Mounting Facility Centers:5.000 inchesMating End Quantity:1Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:20.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:250.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:18.0 single mating end single contact groupingPolarization Method:Mating endShell Type:SolidConnector Locking Method:
5.000 inches Mating End Quantity: 1 Contact Removability: Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 20.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 250.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 18.0 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid
Mating End Quantity:1Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:20.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:250.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:18.0 single mating end single contact groupingPolarization Method:Mating endShell Type:SolidConnector Locking Method:
1Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:20.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:250.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:18.0 single mating end single contact groupingPolarization Method:Mating endShell Type:SolidConnector Locking Method:
Contact Removability:Nonremovable single mating end single contact groupingContact Maximum Current Rating In Amps:20.0 single mating end single contact groupingContact Maximum Ac Voltage Rating In Volts:250.0 single mating end single contact groupingContact Maximum Dc Voltage Rating In Volts:18.0 single mating end single contact groupingPolarization Method:Mating endShell Type:SolidConnector Locking Method:
Nonremovable single mating end single contact grouping Contact Maximum Current Rating In Amps: 20.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 250.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 18.0 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Connector Locking Method:
Contact Maximum Current Rating In Amps: 20.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 250.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 18.0 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Connector Locking Method:
20.0 single mating end single contact grouping Contact Maximum Ac Voltage Rating In Volts: 250.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 18.0 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Connector Locking Method:
Contact Maximum Ac Voltage Rating In Volts: 250.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 18.0 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Connector Locking Method:
250.0 single mating end single contact grouping Contact Maximum Dc Voltage Rating In Volts: 18.0 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Connector Locking Method:
Contact Maximum Dc Voltage Rating In Volts: 18.0 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Connector Locking Method:
18.0 single mating end single contact grouping Polarization Method: Mating end Shell Type: Solid Connector Locking Method:
Polarization Method: Mating end Shell Type: Solid Connector Locking Method:
Mating end Shell Type: Solid Connector Locking Method:
Shell Type: Solid Connector Locking Method:
Solid Connector Locking Method:
Connector Locking Method:
-
Shell twistlock
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Terminal Type:
Solder well single mating end single contact grouping
Included Contact Quantity:
3 single mating end single contact grouping
Included Contact Type:
Round socket single mating end single contact grouping
Shelf Life:
N/a
Unit Of Measure:

Electrical Receptacle Connector - Page 2 of 2



Demilitarization:

No

Fiig:

A039b0