Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-424-9649

| Thread Class:   |
|---|
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Body Style:   |
| Straight shape, external coupling   |
| Overall Length:   |
| 1.215 inches  |
| Overall Height:   |
| Between 1.188 inches and 1.219 inches                                       |
| Overall Width:  |
| Between 1.188 inches and 1.219 inches                                       |
| Environmental Protection:   |
| Pressure proof and moisture resistant and vibration resistant               |
| Unthreaded Mounting Hole Diameter:  |
| Between 0.115 inches and 0.130 inches                                       |
| Center To Center Distance Between Mounting Facilities Parallel To Height:   |
| Between 0.901 inches and 0.911 inches                                       |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| Between 0.901 inches and 0.911 inches                                       |
| Distance From Mounting Shoulder To Front Face:                              |
| Between 0.562 inches and 0.593 inches                                       |
| Threaded Device Type:   |
| Coupling facility   |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 14s-7 single mating end   |
| Contact Removability:   |
| Removable single mating end single contact grouping                         |
| Contact Maximum Current Rating In Amps:                                     |
| 22.0 single mating end single contact grouping                              |
| Contact Maximum Ac Voltage Rating In Volts:                                 |
| 500.0 single mating end single contact grouping                             |
| Contact Maximum Dc Voltage Rating In Volts:                                 |
| 700.0 single mating end single contact grouping                             |
| Polarization Method:  |
| Keyway or multiple keyway   |
| Insert Position In Deg:   |
| 0.0   |
| Shell Type:   |
| Solid   |
|   |

Electrical Receptacle Connector - Page 2 of 2



**Thread Length:** 0.375 inches **Thread Size:** 0.875 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Silver single mating end single contact grouping **Insert Material:** Rubber single mating end **Terminal Type:** Crimp single mating end single contact grouping Shell Material: Aluminum alloy **Shell Surface Treatment:** Cadmium and chromium **Included Contact Quantity:** 3 single mating end single contact grouping Included Contact Type: Round pin single mating end single contact grouping **Precious Material And Location:** Contact surface silver **Precious Material:** Silver **Thread Series Designator:** Unef Shelf Life: N/a Unit Of Measure: ---**Demilitarization:** No Fiig: A039b0