## NSN 5935-00-424-9737

Electrical Plug Connector - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5935-00-424-9737



**Thread Class:** 2a **Thread Direction:** Right-hand **Body Style:** Straight shape, internal coupling **Overall Length:** 1.420 inches **Overall Diameter:** 1.656 inches **Environmental Protection:** Pressure proof and moisture resistant and vibration resistant **Threaded Device Type:** Back shell **Mating End Quantity: Contact Position Arrangement Style:** 22-55 single mating end **Contact Removability:** Removable single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 600.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 218.0 Shell Type: Solid **Connector Locking Method:** Bayonet latch Thread Length: 0.290 inches **Thread Size:** 1.312 inches **Terminal Location:** Back single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping

## **NSN 5935-00-424-9737**Electrical Plug Connector - Page 2 of 2



| Terminal Type:  |
|---|
| Crimp single mating end single contact grouping   |
| Shell Material:   |
| Aluminum alloy  |
| Shell Material Specification:   |
| Qq-a-367 federal specification single material response   |
| Included Contact Quantity:  |
| 55 single mating end single contact grouping  |
| Precious Material And Location:   |
| Contact surface gold  |
| Precious Material And Weight:   |
| 0.055 gold grains, troy   |
| Precious Material:  |
| Gold  |
| Test Data Document:   |
| 81349-mil-c-26482 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificatio |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain         |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                           |
| Thread Series Designator:   |
| Unef  |
| Specification Data:   |
| 96906-ms3476 government standard  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A039b0  |
| Mil-std (military Standard):  |
| Mil-g-45204 spec.   |
| Mil-g-45204 spec.   |