NSN 5935-00-425-4110

Body Style: Straight shape Overall Length:

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-425-4110

1.447 inches
Overall Height:
0.564 inches
Overall Width:
0.614 inches
Unthreaded Mounting Hole Diameter:
0.210 inches
Distance Between Mounting Facility Centers:
1.125 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
9 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
7.5 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
1250.0 single mating end single contact grouping
Contact Maximum Frequency Rating:
60.0 kilohertz single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Potting
Connector Cable Strain Relief Method:
Potting type
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Terminal Location:
Front single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping or silver single mating end single contact grouping
Insert Material:
Plastic diallyl phthalate single mating end
Contact Surface Treatment Specification:

Mil-g-45204 military specification 1st treatment response single mating end single contact grouping or qq-s-365 federal specification 2nd

treatment response single mating end single contact grouping

NSN 5935-00-425-4110

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Crimp single mating end single contact grouping
Contact Material Specification:
Mil-c-24308 military specification single material response single mating end single contact grouping
Shell Material:
Aluminum
Shell Surface Treatment:
Cadmium
Shell Surface Treatment Specification:
Qq-p-416, type 2, cl 3 federal specification single treatment response
Shell Material Specification:
Qq-a-591 federal specification single material response
Insert Material Specification:
Mil-m-14 military specification single material response single mating end
Included Contact Quantity:
9 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Test Data Document:
98230-0n047294 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing,
etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-24308 spec.