## NSN 5935-00-425-6701

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-425-6701 **Body Style:** Right angle type **Overall Length:** 3.344 inches **Overall Height:** 0.720 inches **Overall Width:** 0.470 inches **Environmental Protection:** Humidity resistant and shock resistant and vibration resistant **Unthreaded Mounting Hole Diameter:** 0.156 inches **Distance Between Mounting Facility Centers:** 3.000 inches **Mating End Quantity: Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 7.5 single mating end single contact grouping **Contact Maximum Ac Voltage Rating In Volts:** 725.0 single mating end single contact grouping **Polarization Method:** Mating end Shell Type: Solid **Connector Locking Method:** Friction **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Terminal Type:** Solder well single mating end single contact grouping **Shell Material:** Aluminum

**Shell Surface Treatment:** 

Cadmium and iridium

# NSN 5935-00-425-6701

Electrical Receptacle Connector - Page 2 of 2



### **Shell Material Specification:**

Qq-a-591 federal specification single material response

#### **Insert Material Specification:**

Mil-m-14, ty mdg military specification single material response single mating end

#### **Included Contact Quantity:**

23 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

#### **Precious Material And Location:**

Contact surfaces gold

#### **Precious Material And Weight:**

0.023 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.