

View Online at https://aerobasegroup.com/nsn/5935-00-426-8595

| Thread Class: |
|------------------------------------------------------------------------|
| 2a and 2b |
| Thread Direction: |
| Right-hand and right-hand |
| Body Style: |
| Hood, side opening w/clamp |
| Overall Length: |
| Between 2.713 inches and 2.723 inches |
| Overall Width: |
| Between 0.870 inches and 0.880 inches |
| Environmental Protection: |
| Salt water resistant |
| Cable Entrance Diameter: |
| 0.546 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 50 single mating end |
| Polarization Method: |
| Jackscrew |
| Shell Type: |
| Hood, side opening |
| Connector Locking Method: |
| Jackscrew-socket |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Thread Length: |
| 0.178 inches |
| Thread Size: |
| 0.138 inches and 0.138 inches |
| Shell Material: |
| |
| Shell Surface Treatment: |
| Cadmium |
| Shell Surface Treatment Specification: |
| Qq-p-416, type 2, cl 1 federal specification single treatment response |
| Thread Series Designator: |
| Unc and unc |
| Shelf Life: |
| N/a |

Electrical Plug Connector Body - Page 2 of 2



Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0