

View Online at https://aerobasegroup.com/nsn/5935-00-426-8673

| Thread Class: |
|---|
| 2a and 2b |
| Thread Direction: |
| Right-hand |
| Body Style: |
| Hood, side opening w/clamp |
| Overall Length: |
| 3.137 inches |
| Overall Height: |
| 2.467 inches |
| Overall Width: |
| 1.375 inches |
| Environmental Protection: |
| Humidity resistant and shock resistant and thermal shock resistant and vibration resistant |
| Cable Entrance Diameter: |
| Between 0.859 inches and 0.984 inches |
| Threaded Device Type: |
| Coupling facility |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 75 single mating end |
| Polarization Method: |
| Jackscrew |
| Shell Type: |
| Hood, side opening |
| Connector Locking Method: |
| Jackscrew-socket |
| Connector Cable Strain Relief Method: |
| Cable clamp |
| Thready Qty Per Inch (tpi): |
| 32 |
| Thread Size: |
| 0.138 inches |
| Insert Material: |
| Plastic diallyl phthalate glass filled single mating end |
| Shell Material: |
| Aluminum alloy |
| Shell Surface Treatment: |
| Passivate |
| Insert Material Specification: |
| Mil-m-14, ty sdg-f military specification single material response or mil-p-19833, type gdi-30f military specification single material response |

single mating end



Thread Series Designator:

Unc

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-m-14 spec.