

View Online at https://aerobasegroup.com/nsn/5935-00-426-8689

| Thread Class: |
|---|
| 2a and 2b and 2a |
| Thread Direction: |
| Right-hand and right-hand and right-hand |
| Body Style: |
| Rectangular shape |
| Overall Length: |
| 3.005 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| Between 2.371 inches and 2.379 inches |
| Overall Height: |
| 0.916 inches |
| Overall Width: |
| 1.732 inches |
| Environmental Protection: |
| Salt water resistant |
| Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: |
| Between 0.870 inches and 0.880 inches |
| Threaded Device Type: |
| Coupling facility and mounting stud |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 25-104 single mating end |
| Polarization Method: |
| Jackscrew and shell |
| Shell Type: |
| Solid |
| Connector Locking Method: |
| Jackscrew-socket |
| Thread Length: |
| 0.172 inches and 0.172 inches and 0.255 inches |
| Thready Qty Per Inch (tpi): |
| 32 and 32 and 32 |
| Thread Size: |
| 0.164 inches and 0.164 inches and 0.138 inches |
| Shell Surface Treatment: |
| Cadmium |
| Shell Surface Treatment Specification: |
| Qq-p-416, type 2, cl 1 federal specification single treatment response |
| Shell Guide Type And Location Designator: |
| A slot |



Unable To Decode:

Unable to decode and unable to decode

Thread Series Designator:

Unc and unc and unc

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0