# NSN 5935-00-426-9041

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-426-9041

The common of th
Body Style:
Straight shape, flush mount
Overall Length:
1.395 inches
Overall Height:
1.170 inches
Overall Width:
4.325 inches
Environmental Protection:
Corrosion resistant and thermal shock resistant and vibration resistant and shock resistant and moisture resistant and pressure proof
Unthreaded Mounting Hole Diameter:
0.138 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
Between 0.558 inches and 0.566 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
Between 3.671 inches and 3.879 inches
Distance From Mounting Shoulder To Front Face:
Between 0.518 inches and 0.534 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
101 single mating end
Contact Removability:
Removable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Polarization Method:
Mating end
Shell Type:
Solid
Connector Locking Method:
Friction
Operating Tempurature Rating:
Between -65.0 degrees celsius and 200.0 degrees celsius
Terminal Location:

Back single mating end single contact grouping

### **Contact Material:**

Copper alloy single mating end single contact grouping

### **Contact Surface Treatment:**

Gold single mating end single contact grouping and copper single mating end single contact grouping

#### **Insert Material:**

Plastic diallyl phthalate glass filled single mating end or plastic phenolic mineral filled single mating end or plastic polyester glass filled single mating end

# NSN 5935-00-426-9041

Electrical Receptacle Connector - Page 2 of 2



#### **Contact Surface Treatment Specification:**

Mil-q-45204 military specification 1st treatment response single mating end single contact grouping

#### **Terminal Type:**

Crimp single mating end single contact grouping

#### **Contact Material Specification:**

Qq-c-533 federal specification single material response single mating end single contact grouping

#### **Shell Material:**

Aluminum alloy a380.0

#### **Shell Surface Treatment:**

Nickel alloy

#### **Shell Surface Treatment Specification:**

Mil-c-26074, claas 3 military specification single treatment response

#### **Shell Material Specification:**

Qq-a-591 federal specification single material response

#### **Insert Material Specification:**

Mil-m-14 military specification all material responses single mating end

#### **Included Contact Quantity:**

101 single mating end single contact grouping

#### **Included Contact Type:**

Round pin single mating end single contact grouping

## **Precious Material And Location:**

Contact surfaces gold

## **Precious Material And Weight:**

0.101 gold grains, troy

## Precious Material:

Gold

#### Shelf Life:

N/a

#### **Unit Of Measure:**

--

#### Demilitarization:

No

## Fiig:

A039b0

#### Mil-std (military Standard):

Mil-g-45204 spec.