Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-430-3852

Thread Class:
2a
Thread Direction:
Right-hand
Body Style:
Straight shape, internal coupling
Overall Length:
Between 1.035 inches and 1.100 inches
Overall Diameter:
Between 1.205 inches and 1.225 inches
Environmental Protection:
Pressure proof and moisture resistant and vibration resistant
Threaded Device Type:
Back shell
Mating End Quantity:
1
Contact Position Arrangement Style:
"14-4, 14-04" single mating end
Contact Removability:
Removable single mating end single contact grouping
Polarization Method:
Key, multiple key groove
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Bayonet latch
Thready Qty Per Inch (tpi):
28
Thread Size:
0.875 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping
Contact Surface Treatment Specification:
Mil-g-45204, type 1, class 1 military specification single treatment response single mating end single contact grouping
Terminal Type:
Crimp single mating end single contact grouping

NSN 5935-00-430-3852

--

Electrical Plug Connector - Page 2 of 2



Shell Material: Aluminum alloy 6061 **Shell Surface Treatment:** Cadmium **Shell Surface Treatment Specification:** Qq-p-416, type 2, cl 3 federal specification single treatment response **Shell Material Specification:** Qq-a-367, t6 federal specification single material response **Included Contact Quantity:** 4 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.020 gold grains, troy **Precious Material:** Gold **Test Data Document:** 81349-mil-c-81511 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:** Un **Specification Data:** 81349-mil-c-81511/6 government specification Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: A039b0 Mil-std (military Standard): Mil-g-45204 spec.