

View Online at <https://aerobasegroup.com/nsn/5935-00-431-4908>

Body Style:

Straight shape, external coupling w/backshell

Overall Length:

1.280 inches

Overall Height:

1.453 inches

Overall Width:

1.453 inches

Environmental Protection:

Heat resistant and salt water resistant and vibration resistant

Unthreaded Mounting Hole Diameter:

0.120 inches

Center To Center Distance Between Mounting Facilities Parallel To Height:

Between 1.137 inches and 1.237 inches

Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:

Between 1.137 inches and 1.237 inches

Distance From Mounting Shoulder To Front Face:

0.526 inches

Mating End Quantity:

1

Contact Position Arrangement Style:

37p single mating end

Contact Removability:

Removable single mating end single contact grouping

Contact Maximum Current Rating In Amps:

5.0 single mating end single contact grouping

Polarization Method:

Keyway or multiple keyway

Insert Position In Deg:

0.0

Shell Type:

Solid

Connector Locking Method:

Detent

Terminal Location:

Back single mating end single contact grouping

Contact Material:

Copper alloy single mating end single contact grouping

Contact Surface Treatment:

Gold single mating end single contact grouping

Insert Material:

Plastic diallyl phthalate single mating end

Contact Surface Treatment Specification:

Mil-g-45204, type 2, class 2, military specification single treatment response single mating end single contact grouping

Terminal Type:

Crimp single mating end single contact grouping

Shell Material:

Aluminum alloy

Insert Material Specification:

Mil-m-14 military specification single material response single mating end

Included Contact Quantity:

37 single mating end single contact grouping

Included Contact Type:

Round pin single mating end single contact grouping

Precious Material And Location:

Contact surfaces gold

Precious Material And Weight:

0.037 gold grains, troy

Precious Material:

Gold

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.