## NSN 5935-00-431-5228

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-431-5228

Thread Direction: Right-hand Body Style: Straight shape, internal coupling Overall Length: 1.484 inches Overall Diameter: 0.813 inches Cable Entrance Diameter: 0.261 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Removable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method: Crimp type
Right-hand Body Style: Straight shape, internal coupling Overall Length: 1.484 inches Overall Diameter: 0.813 inches Cable Entrance Diameter: 0.261 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Removable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method:
Body Style: Straight shape, internal coupling Overall Length: 1.484 inches Overall Diameter: 0.813 inches Cable Entrance Diameter: 0.261 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Removable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method:
Straight shape, internal coupling  Overall Length:  1.484 inches  Overall Diameter:  0.813 inches  Cable Entrance Diameter:  0.261 inches  Threaded Device Type:  Coupling facility  Mating End Quantity:  1  Contact Position Arrangement Style:  N single mating end  Contact Removability:  Removable single mating end single contact grouping  Shell Type:  Solid  Connector Locking Method:  Internally threaded coupling ring  Connector Cable Strain Relief Method:
Overall Length:  1.484 inches  Overall Diameter:  0.813 inches  Cable Entrance Diameter:  0.261 inches  Threaded Device Type:  Coupling facility  Mating End Quantity:  1  Contact Position Arrangement Style:  N single mating end  Contact Removability:  Removable single mating end single contact grouping  Shell Type:  Solid  Connector Locking Method:  Internally threaded coupling ring  Connector Cable Strain Relief Method:
1.484 inches  Overall Diameter: 0.813 inches  Cable Entrance Diameter: 0.261 inches  Threaded Device Type: Coupling facility  Mating End Quantity: 1  Contact Position Arrangement Style: N single mating end  Contact Removability: Removable single mating end single contact grouping  Shell Type: Solid  Connector Locking Method: Internally threaded coupling ring  Connector Cable Strain Relief Method:
Overall Diameter:  0.813 inches  Cable Entrance Diameter:  0.261 inches  Threaded Device Type:  Coupling facility  Mating End Quantity:  1  Contact Position Arrangement Style:  N single mating end  Contact Removability:  Removable single mating end single contact grouping  Shell Type:  Solid  Connector Locking Method:  Internally threaded coupling ring  Connector Cable Strain Relief Method:
Cable Entrance Diameter:  0.261 inches Threaded Device Type: Coupling facility Mating End Quantity:  1 Contact Position Arrangement Style: N single mating end Contact Removability: Removable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method:
Cable Entrance Diameter:  0.261 inches Threaded Device Type: Coupling facility Mating End Quantity:  1 Contact Position Arrangement Style: N single mating end Contact Removability: Removable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method:
O.261 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: N single mating end Contact Removability: Removable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method:
Threaded Device Type: Coupling facility  Mating End Quantity:  1 Contact Position Arrangement Style: N single mating end Contact Removability: Removable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method:
Coupling facility  Mating End Quantity:  1  Contact Position Arrangement Style: N single mating end  Contact Removability: Removable single mating end single contact grouping  Shell Type: Solid  Connector Locking Method: Internally threaded coupling ring  Connector Cable Strain Relief Method:
Mating End Quantity:  1  Contact Position Arrangement Style:  N single mating end  Contact Removability:  Removable single mating end single contact grouping  Shell Type:  Solid  Connector Locking Method:  Internally threaded coupling ring  Connector Cable Strain Relief Method:
Contact Position Arrangement Style:  N single mating end Contact Removability: Removable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method:
Contact Position Arrangement Style:  N single mating end  Contact Removability:  Removable single mating end single contact grouping  Shell Type:  Solid  Connector Locking Method:  Internally threaded coupling ring  Connector Cable Strain Relief Method:
N single mating end  Contact Removability:  Removable single mating end single contact grouping  Shell Type:  Solid  Connector Locking Method:  Internally threaded coupling ring  Connector Cable Strain Relief Method:
Contact Removability: Removable single mating end single contact grouping Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method:
Removable single mating end single contact grouping  Shell Type:  Solid  Connector Locking Method:  Internally threaded coupling ring  Connector Cable Strain Relief Method:
Shell Type: Solid Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method:
Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method:
Connector Locking Method: Internally threaded coupling ring Connector Cable Strain Relief Method:
Internally threaded coupling ring  Connector Cable Strain Relief Method:
Connector Cable Strain Relief Method:
Crimp type
Radio Frequency Type Contact Characteristic Impedance In Ohms:
50.0 single mating end single contact grouping
Thread Size:
0.625 inches
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and copper single mating end single contact grouping
Insert Material:
Plastic tetrafluoroethylene single mating end
Terminal Type:
Crimp single mating end single contact grouping
Shell Material:
Copper alloy

## **NSN 5935-00-431-5228**Electrical Plug Connector - Page 2 of 2



Shell Surface Treatment:
Gold and copper
Included Contact Quantity:
1 single mating end single contact grouping
Included Contact Type:
Coaxial pin single mating end single contact grouping
Precious Material And Location:
Contact and shell surface gold
Precious Material And Weight:
0.105 gold grains, troy
Precious Material:
Gold
Thread Series Designator:
Unef
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0