Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-431-7855

## **Body Style:** Right angle type **Overall Length:** Between 1.550 inches and 1.570 inches **Overall Width:** Between 0.245 inches and 0.255 inches **Body Height:** 0.250 inches **Unthreaded Mounting Hole Diameter:** Between 0.088 inches and 0.098 inches **Distance Between Mounting Facility Centers:** Between 1.245 inches and 1.255 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 6 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Contact **Terminal Location:** Side single mating end single contact grouping **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Gold single mating end single contact grouping **Insert Material:** Plastic diallyl phthalate single mating end **Contact Surface Treatment Specification:** Mil-g-45204 military specification single treatment response single mating end single contact grouping **Terminal Type:** Pin single mating end single contact grouping **Insert Material Specification:** Mil-m-19833, type gdi-30f military specification single material response single mating end **Included Contact Quantity:** 6 single mating end single contact grouping **Included Contact Type:** Round socket single mating end single contact grouping

## Precious Material And Location:

Contact surfaces gold



**Precious Material And Weight:** 

0.006 gold grains, troy

**Precious Material:** 

Gold

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-g-45204 spec.