NSN 5935-00-432-0860

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-432-0860

| View Offiline at https://derobasegroup.com/nsn/3333-00-432-0000 |
|--|
| Body Style: |
| Straight shape |
| Overall Length: |
| 0.875 inches |
| Overall Height: |
| 0.576 inches |
| Overall Width: |
| 0.625 inches |
| Mating End Quantity: |
| 1 |
| Contact Position Arrangement Style: |
| 12 single mating end |
| Contact Removability: |
| Nonremovable single mating end all contact groupings |
| Contact Maximum Current Rating In Amps: |
| 5.0 single mating end all contact groupings |
| Contact Maximum Ac Voltage Rating In Volts: |
| 250.0 single mating end all contact groupings |
| Connector Locking Method: |
| Friction |
| Operating Tempurature Rating: |
| Between -40.0 degrees celsius and 105.0 degrees celsius |
| Terminal Location: |
| Back single mating end all contact groupings |
| Contact Material: |
| Copper alloy single mating end all contact groupings |
| Contact Surface Treatment: |
| Gold single mating end all contact groupings |
| Insert Material: |
| Plastic polyamide single mating end |
| Contact Surface Treatment Specification: |
| Mil-g-45204 military specification single treatment response single mating end all contact groupings |
| Terminal Type: |
| Printed circuit single mating end all contact groupings |
| Included Contact Quantity: |
| 11 single mating end 2nd contact grouping |
| Included Contact Type: |
| Round socket single mating end 1st contact grouping |
| Precious Material And Location: |

Contact surfaces gold

Precious Material And Weight:

0.012 gold grains, troy

NSN 5935-00-432-0860

Electrical Receptacle Connector - Page 2 of 2



| Precious Material: |
|------------------------------|
| Gold |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A039b0 |
| Mil-std (military Standard): |

Mil-g-45204 spec.