## NSN 5935-00-432-5948

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-432-5948

Body Style:
Straight shape, external coupling w/backshell
Overall Length:
0.844 inches
Overall Height:
1.296 inches
Overall Width:
1.296 inches
Unthreaded Mounting Hole Diameter:
0.120 inches
Center To Center Distance Between Mounting Facilities Parallel To Height:
0.968 inches
Distance Between Centerlines Of Mounting Facilities Parallel To Body Width:
0.968 inches
Distance From Mounting Shoulder To Front Face:
0.546 inches
Mating End Quantity:
1
Contact Position Arrangement Style:
27-30 single mating end
Contact Removability:
Nonremovable single mating end single contact grouping
Contact Maximum Current Rating In Amps:
5.0 single mating end single contact grouping
Contact Maximum Ac Voltage Rating In Volts:
250.0 single mating end single contact grouping
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Spring friction
Terminal Location:
Back single mating end single contact grouping
Contact Material:
Copper alloy single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping

Insert Material:

Rubber synthetic single mating end

## NSN 5935-00-432-5948

Electrical Receptacle Connector - Page 2 of 2



Terminal Type:
Solder well single mating end single contact grouping
Shell Material:
Aluminum alloy
Shell Surface Treatment:
Cadmium
Included Contact Quantity:
91 single mating end single contact grouping
Included Contact Type:
Round pin single mating end single contact grouping
Precious Material And Location:
Contact surfaces gold
Precious Material And Weight:
0.091 gold grains, troy
Precious Material:
Gold
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A039b0