## NSN 5935-00-432-6245

Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-432-6245

| View Online at https://aerobasegroup.com/nsn/5935-00-432-6245   |
|---|
| Body Style:   |
| Straight shape  |
| Overall Length:   |
| 1.480 inches  |
| Overall Height:   |
| 0.200 inches  |
| Overall Width:  |
| 0.115 inches  |
| Environmental Protection:   |
| Vibration proof and shock proof and heat resistant and cold resistant and salt water resistant and moisture resistant |
| Mating End Quantity:  |
| 1   |
| Contact Position Arrangement Style:   |
| 1 row of contacts non-inserted board single mating end  |
| Contact Removability:   |
| Removable single mating end single contact grouping   |
| Contact Maximum Current Rating In Amps:   |
| 5.0 single mating end single contact grouping   |
| Connector Locking Method:   |
| Friction  |
| Terminal Location:  |
| Back single mating end single contact grouping  |
| Contact Material:   |
| Copper alloy single mating end single contact grouping  |
| Contact Surface Treatment:  |
| Gold single mating end single contact grouping  |
| Insert Material:  |
| Glass fiber single mating end and plastic single mating end   |
| Contact Surface Treatment Specification:  |
| Mil-g-45204 military specification single treatment response single mating end single contact grouping                |
| Terminal Type:  |
| Crimp single mating end single contact grouping   |
| Included Contact Quantity:  |
| 15 single mating end single contact grouping  |
| Included Contact Type:  |
| Round socket single mating end single contact grouping  |
| Precious Material And Location:   |
| Contact surfaces gold   |
| Precious Material And Weight:   |
| 0.015 gold grains, troy   |
| Precious Material:  |

Gold

## NSN 5935-00-432-6245

Electrical Plug Connector - Page 2 of 2



| Shelf Life:       |
|-------------------|
| N/a               |
| Unit Of Measure:  |
|                   |
| Demilitarization: |
| No                |
| Fiig:             |
| A039b0            |

Mil-std (military Standard):

Mil-g-45204 spec.