Electrical Plug Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-432-6492

2b <b>Thread Direction:</b> Right-hand <b>Body Style:</b> Angle shape w/cable clamp <b>Overall Diameter:</b> Between 1.115 inches and 1.135 inches <b>Body Angle In Deg:</b> 90.0 <b>Cable Entrance Diameter:</b> Between 0.230 inches and 0.438 inches <b>Threaded Device Type:</b> Coupling facility <b>Mating End Quantity:</b> 11 <b>Contact Position Arrangement Style:</b> 14s-7 single mating end <b>Konremovable single mating end single contact grouping</b>
Right-handBody Style:Angle shape w/cable clampOverall Diameter:Between 1.115 inches and 1.135 inchesBody Angle In Deg:90.0Cable Entrance Diameter:Between 0.230 inches and 0.438 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Position Arrangement Style:14s-7 single mating endContact Removability:
Body Style:Angle shape w/cable clampOverall Diameter:Between 1.115 inches and 1.135 inchesBody Angle In Deg:90.0Cable Entrance Diameter:Between 0.230 inches and 0.438 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Position Arrangement Style:14s-7 single mating endContact Removability:
Body Style:Angle shape w/cable clampOverall Diameter:Between 1.115 inches and 1.135 inchesBody Angle In Deg:90.0Cable Entrance Diameter:Between 0.230 inches and 0.438 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Position Arrangement Style:14s-7 single mating endContact Removability:
Angle shape w/cable clampOverall Diameter:Between 1.115 inches and 1.135 inchesBody Angle In Deg:90.0Cable Entrance Diameter:Between 0.230 inches and 0.438 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Position Arrangement Style:14s-7 single mating endContact Removability:
Overall Diameter:Between 1.115 inches and 1.135 inchesBody Angle In Deg:90.0Cable Entrance Diameter:Between 0.230 inches and 0.438 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Position Arrangement Style:14s-7 single mating endContact Removability:
Between 1.115 inches and 1.135 inches Body Angle In Deg: 90.0 Cable Entrance Diameter: Between 0.230 inches and 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 14s-7 single mating end Contact Removability:
Body Angle In Deg:90.0Cable Entrance Diameter:Between 0.230 inches and 0.438 inchesThreaded Device Type:Coupling facilityMating End Quantity:1Contact Position Arrangement Style:14s-7 single mating endContact Removability:
90.0 Cable Entrance Diameter: Between 0.230 inches and 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 14s-7 single mating end Contact Removability:
Cable Entrance Diameter:         Between 0.230 inches and 0.438 inches         Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         14s-7 single mating end         Contact Removability:
Between 0.230 inches and 0.438 inches Threaded Device Type: Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 14s-7 single mating end Contact Removability:
Threaded Device Type:         Coupling facility         Mating End Quantity:         1         Contact Position Arrangement Style:         14s-7 single mating end         Contact Removability:
Coupling facility Mating End Quantity: 1 Contact Position Arrangement Style: 14s-7 single mating end Contact Removability:
Mating End Quantity:         1         Contact Position Arrangement Style:         14s-7 single mating end         Contact Removability:
1         Contact Position Arrangement Style:         14s-7 single mating end         Contact Removability:
14s-7 single mating end Contact Removability:
14s-7 single mating end Contact Removability:
Contact Removability:
Polarization Method:
Keyway or multiple keyway
Insert Position In Deg:
0.0
Shell Type:
Solid
Connector Locking Method:
Internally threaded coupling ring
Connector Cable Strain Relief Method:
Cable clamp
Distance From Centerline To Connector End:
2.063 inches
Distance From Centerline To Cable End:
1.550 inches
Thread Length:
0.531 inches
Thread Size:
0.875 inches
Terminal Location:
Back single mating end single contact grouping
Contact Surface Treatment:
Gold single mating end single contact grouping and silver single mating end single contact grouping

NSN 5935-00-432-6492

Electrical Plug Connector - Page 2 of 2



Terminal Type:

Solder well single mating end single contact grouping

Shell Material:

Aluminum alloy

Shell Surface Treatment:

Cadmium

Included Contact Quantity:

3 single mating end single contact grouping

Included Contact Type:

Round socket single mating end single contact grouping

**Precious Material And Location:** 

Contact surfaces gold and contact surfaces silver

**Precious Material And Weight:** 

0.015 gold grains, troy and 0.015 silver grains, troy

Precious Material:

Gold and silver

#### **Test Data Document:**

49956-350062 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.;

excludes any specification, standard or other document that may be referenced in a basic governing drawing)

# **Thread Series Designator:**

Unef

# **Specification Data:**

49956-350062-4 manufacturers specification

### Shelf Life:

N/a

### Unit Of Measure:

---

# Demilitarization:

No

### Fiig:

A039b0