Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-432-9197

## **Body Style:** Straight shape, external coupling **Overall Length:** 1.097 inches **Overall Height:** Between 1.115 inches and 1.136 inches **Overall Width:** Between 1.115 inches and 1.136 inches **Environmental Protection:** Moisture resistant and vibration resistant and salt water resistant **Unthreaded Mounting Hole Diameter:** Between 0.115 inches and 0.125 inches Center To Center Distance Between Mounting Facilities Parallel To Height: 0.906 inches Distance Between Centerlines Of Mounting Facilities Parallel To Body Width: 0.906 inches **Distance From Mounting Shoulder To Front Face:** Between 0.431 inches and 0.441 inches Mating End Quantity: 1 **Contact Position Arrangement Style:** 14-18 single mating end **Contact Removability:** Nonremovable single mating end single contact grouping **Contact Maximum Current Rating In Amps:** 5.0 single mating end single contact grouping **Polarization Method:** Keyway or multiple keyway **Insert Position In Deg:** 90.0 Shell Type: Solid **Connector Locking Method:** Bayonet pin **Terminal Location:**

Back single mating end single contact grouping

## **Contact Material:**

Copper alloy single mating end single contact grouping

## **Contact Surface Treatment:**

Gold single mating end single contact grouping

## **Terminal Type:**

Solder well single mating end single contact grouping



**Shell Material:** Aluminum alloy Shell Surface Treatment: Cadmium Included Contact Quantity: 18 single mating end single contact grouping **Included Contact Type:** Round pin single mating end single contact grouping **Precious Material And Location:** Contact surfaces gold **Precious Material And Weight:** 0.018 gold grains, troy **Precious Material:** Gold Shelf Life: N/a Unit Of Measure: ---Demilitarization: No Fiig: A039b0