## NSN 5935-00-432-9340

Electrical Receptacle Connector - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-432-9340 **Thread Class:** 2a **Thread Direction:** Right-hand **Overall Length:** 1.132 inches **Overall Height:** 1.375 inches **Overall Width:** 0.750 inches **Distance From Mounting Shoulder To Front Face:** Between 0.296 inches and 0.328 inches **Threaded Device Type:** Mounting bushing **Mating End Quantity: Contact Position Arrangement Style:** Nonstd single mating end **Contact Removability:** Nonremovable single mating end single contact grouping Shell Type: Solid Thread Length: 0.312 inches Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.375 inches **Contact Material:** Copper alloy single mating end single contact grouping **Contact Surface Treatment:** Cadmium single mating end single contact grouping **Contact Surface Treatment Specification:** Qq-p-416, type 2, cl 1 federal specification single treatment response single mating end single contact grouping **Contact Material Specification:** Qq-b-750, comp a, spring federal specification single material response single mating end single contact grouping **Shell Material:** Copper alloy **Shell Surface Treatment:** 

Cadmium

Shell Surface Treatment Specification:

Qq-p-416, type 2, cl 3 federal specification single treatment response

## NSN 5935-00-432-9340

Electrical Receptacle Connector - Page 2 of 2



Included Contact Quantity
---------------------------

1 single mating end single contact grouping

**Bushing Accommodation Hole Shape:** 

Round

**Included Contact Type:** 

Round socket single mating end single contact grouping

**Test Data Document:** 

96906-ms90298 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Thread Series Designator:
---------------------------

Unef

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A039b0

Mil-std (military Standard):

Mil-c-83413 spec.