NSN 5935-00-433-5778

Telephone Jack - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5935-00-433-5778 **Thread Class:** 2a **Thread Direction:** Right-hand **Electrical Insulation Feature:** Insulated from panel **Body Style:** Threaded bushing mounted long frame **Overall Length:** 3.172 inches **Overall Height:** 1.125 inches **Mounting Hole Diameter:** 0.156 inches **Mounting Bushing Length:** 0.375 inches **Body Width:** 0.375 inches **Bushing Accommodation Hole Shape:** Round **Accommodated Finger Type:** Three conductor, slender spherical tip single finger **Finger Accommodation Diameter:** 0.207 inches single finger **Finger Accommodation Length:** 1.093 inches single finger **Bushing Thru-hole Accommodation Diameter:** 0.375 inches **Jack Contact Arrangement Designator:** J7 **Mounting Facility Type And Quantity:** 1 bushing Thready Qty Per Inch (tpi): 32 **Thread Size:** 0.375 inches **Terminal Type:** Tab, solder lug Material:

Any acceptable terminal

Surface Treatment:

Any acceptable contact

NSN 5935-00-433-5778

Telephone Jack - Page 2 of 2



Test Data Document:

81349-mil-j-641 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Ihread	Series	Designator:
Unef		

81349-mil-j-641 government specification

Shelf Life:

N/a

Unit Of Measure:

Specification Data:

--

Demilitarization:

No

Fiig:

A03400